




CONNEX ELECTRIC MOTORS

CCITIR12-213-003

High Efficiency Cast Iron * TEFC * Three Phase Motor

Design C Meets NEMA MG-1 * IP55 Protection * High Torque * Inverter Rated



DIMENSIONAL DATA

MOUNTING							CONDUIT BOX		C-FLANGE		
D	E	2F	A	B	BA	H	AB	AA	AJ	AK	N
5.25	4.25	5.5	11	7.87	3.5	0.41	8.3	1	7.25	8.5	3.12
MOTOR DIMENSIONS					KEYSEAT				BEARING		
C	O	P	T	N-W	U	R	S	ES	DE	ODE	ENCLO.
18.9	10.5	10.5	1.9	3.38	1.375	1.201	0.312	2.41	6308ZZ	6306ZZ	TEFC

PERFORMANCE DATA

50/60 Hz * Class F Insulation * 40°C Ambient * Continuous Duty * 1.15 Service Factor

HP	Frame	Full Load RPM	Efficiency%			Power Factor		Amps@460V		Full Load Torque	Locked Rotor Torque %FLT	Full Out Torque %FLT	APP. WEIGHT
			100% F.L.	75% F.L.	50% F.L.	100% F.L.	75% F.L.	Full Load	Locked Rotor				
3	213T	1170	87.5	87	85	74	67	8.8/4.4	32	13.47	250	320	155.87
VAC	208-230/460V		INVERTER RATED 10:1										

CONNEX INDUSTRIAL CORP.

4975 AVALON RIDGE PKWY, SUITE 200, PEACHTREE CORNER, GA 30071

TOLL FREE: 1-877-884-2910 TEL: 770-248-9588 FAX: 770-248-9589

www.connex-electric.com