




CONNEX ELECTRIC MOTORS

CCITIR12-404-060

High Efficiency Cast Iron * TEFC * Three Phase Motor

Design C Meets NEMA MG-1 * IP55 Protection * High Torque * Inverter Rated



DIMENSIONAL DATA

MOUNTING							CONDUIT BOX		C-FLANGE		
D	E	2F	A	B	BA	H	AB	AA	AJ	AK	N
10	8	12.25	19.3	17.9	6.62	0.81	15.6	3	11	12.5	7
MOTOR DIMENSIONS					KEYSEAT			BEARING			
C	O	P	T	N-W	U	R	S	ES	DE	ODE	ENCLO.
38.2	19.8	19.8	3	7.25	2.875	2.45	0.75	5.65	NU316	6313C3	TEFC

PERFORMANCE DATA

50/60 Hz * Class F Insulation * 40°C Ambient * Continuous Duty * 1.15 Service Factor

HP	Frame	Full Load RPM	Efficiency%			Power Factor		Amps@460V		Full Load Torque	Locked Rotor Torque %FLT	Full Out Torque %FLT	APP. WEIGHT
			100% F.L.	75% F.L.	50% F.L.	100% F.L.	75% F.L.	Full Load	Locked Rotor				
60	404T	1170	93.6	93.5	93	86	83	146/73	435	266	200	250	1081.74
VAC	208-230/460V		INVERTER RATED 10:1										

CONNEX INDUSTRIAL CORP.

4975 AVALON RIDGE PKWY, SUITE 200, PEACHTREE CORNER, GA 30071

TOLL FREE: 1-877-884-2910 TEL: 770-248-9588 FAX: 770-248-9589

www.connex-electric.com