




CONNEX ELECTRIC MOTORS

CRSTF18-056-12-SL

Roll Steel * Single Phase * Farm Duty Motor

NEMA Design B * High Efficiency * High Starting Torque * Removable Feet



DIMENSIONAL DATA

MOUNTING							CONDUIT BOX			BEARING	
D	E	2F	A	B	BA	H	AB	XL	XN	DE	ODE
3.5	2.44	3	6.5	6.5	2.75	1.22X.34	5.315	3.78	3.31	6203	6203
MOTOR DIMENSIONS							KEYSEAT				
AH	AJ	AK	P	O	OX	N-W	U	R	S	KEY	C DIM.
1.88	5.875	4.5	7.44	6.5	7.5	1.88	0.625	0.516	0.188	1.42	12.3

PERFORMANCE DATA

50/60 Hz * Class F Insulation * 40°C Ambient * Continuous Duty * 1.15 Service Factor

HP	FRAME	FULL LOAD RPM	EFF.	P. F	FULL LOAD AMPS	LOCKED ROTOR AMPS	VAC	LRT /TN	BRT /TN	TYPE	WGT
1/2	56C	1725	64	0.56	8.8/4.2	40.5/23.4	115/230V	3.18	3.05	CSIR	30

CONNEX INDUSTRIAL CORP.

4975 AVALON RIDGE PKWY, SUITE 200, PEACHTREE CORNER, GA 30071

TOLL FREE: 1-877-884-2910 TEL: 770-248-9588 FAX: 770-248-9589

www.connex-electric.com