




CONNEX ELECTRIC MOTORS

CSSTR12-213-03

Stainless Steel * TEFC * Three Phase Motor

NEMA Design B * High Efficiency * IP55 Protection * Squirrel Cage AC Motor



DIMENSIONAL DATA

MOUNTING							CONDUIT BOX				
D	E	2F	A	B	BA	H	AB	AC	XL	XN	AA
5.25	4.25	5.5	10	8.5	4.25	.71x.47	7.6	6.2	4.45	4.05	0.94
MOTOR DIMENSIONS					KEYSEAT			BEARING		ENCL.	
C	AH	AJ	AK	N-W	U	R	S	KEY	DE		ODE
21.5	3.12	7.25	8.5	3.38	1.375	1.201	0.312	2.41	6308zz	6208zz	TEFC

PERFORMANCE DATA

50/60 Hz * Class F Insulation * 40°C Ambient * Continuous Duty * 1.15 Service Factor

HP	Frame	Full Load RPM	Efficiency%			Power Factor		Amps@460V		Full Load Torque	Locked Rotor Torque %FLT	Full Out Torque %FLT	APP. WEIGHT
			100% F.L.	75% F.L.	50% F.L.	100% F.L.	75% F.L.	Full Load	Locked Rotor				
3	213TC	1175	87.5%	82%	77%	0.74	0.67	4.3	21	13.2	210%	280%	178
VAC	208-230/460V												

CONNEX INDUSTRIAL CORP.

4975 AVALON RIDGE PKWY, SUITE 200, PEACHTREE CORNER, GA 30071

TOLL FREE: 1-877-884-2910 TEL: 770-248-9588 FAX: 770-248-9589

www.connex-electric.com